



## **Mondosport II**







MONDOSPORT II - Texture

MONDOSPORT II - Backing

MONDOSPORT II WOOD

Vinyl Point Elastic multi-purpose sports flooring.

The flooring is comprised of a surface layer with embossed, matt and non-slip finish, coupled to an elastic polyurethane foam subsurface of constant thickness.

The two-layered structure gives the flooring modulated density and hardness to ensure the correct distribution of loads, energy return and shock absorption produced during sports activities.

The floor can be glued directly on a suitable subsurface or installed to the stabilising underlayment Everlay with a suitable adhesive. Technical characteristics in accordance with the EN 14904 standard.

## Schock absorption level >25%

Mondosport II, in combination with the underlayment Everlay, ensures a level of shock absorption greater than 25%

## Mondosport II + Everlay = Waterproof coupling

Mondosport II can be combined to the waterproofing underlayment Everlay during installation that is dry laid on a suitable subsurface. The combination is effective against moisture problems and prevents the formation of surface bubbles.

SUITABLE FOR

## **REFERENCES**

Any reproduction, either partial or total, including the transmission of the data set out in this document shall be authorized in writing and in advance by Mondo. Mondo has the right to modify either specifications and products at any time, without notice. This document is not legally binding as a contract.

REV. 00 April 2011 Page 2 of 3

**COLOR RANGE** 

**DIMENSIONS** 

REV. 00 April 2011